# **Audley**

- · Crackle gloss tiles
- Suitable for internal wall applications
- Flat and bevelled tiles



GRESTEC.CO.UK / 0345 130 2241




















ADE0623 LRV: 54 ADE32517 LRV: 53 ADE32519 LRV: 37 ADE0630 LRV: 13 ADE32518 LRV: 17 ADE0629 LRV: 4

13

ADE0626 LRV: 33

ADE0624 LRV: 54



0		=		h			P		
	DECORS / SPECIAL PIECES (MM)	ADE0623	ADE32517	ADE32519	ADE0630	ADE32518	ADE0629	ADE0626	ADE0624
9	75×150 BIZ								
10	75X150 MAR								
11	75x150 OLAS								
12	75x150 CLASSIC								
13	150x150 RODAPIE + ANGLE				Ξ				
14	50x150 MOLDURA ITAL + ANGLES								
15	75x150 CORNISA CLASSIC + ANGLES				Ξ				
16	25x150 CUBRECANTO + ANGLE								
17	8.5x150 / 8.5x200 BULLNOSE								



## **TECHNICAL SPECIFICATION**

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES		
Water absorption	ISO 10545-3	> 10% Group BLL		
Bending strength	ISO 10545-4	RM > 150 kg/cm <sup>2</sup>		
Resistance to chemical products	ISO 10545-13	Resistant		
Stain resistance	ISO 10545-14	Resistant		
Crazing resistance	ISO 10545-11	Resistant		
Scratch hardness (MOHS scale)	EN 101	Gloss - hardness 4 Matt - hardness 5		

## **CLEANING + MAINTENANCE ADVICE**

#### **BEFORE GROUTING**

A pre grout protector Fila PRW200 is advised to protect the tiles; this is a temporary seal that when cleaning the grout will wash off.

## **INITIAL WASHING**

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul> <li>Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure.</li> <li>Polish wall tiling with a dry cloth when joints are hard.</li> </ul>

## **IMPREGNATING**

It is also recommended to seal the body of the tiles with Fila MP90.

## ROUTINE MAINTENACE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)			
Equipment	Cloth			
Procedure	<ul> <li>Remove dust with a dry cloth</li> <li>Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well</li> </ul>			

