





Earthbound

The Earthbound series showcases the artistry of traditional craftsmanship. Each piece is distinguished by intentionally crafted irregular edges and dimensional variations, lending an authentic, handmade appearance. These characteristics make every item unique. To maintain this distinctiveness, a grout line of at least 2mm is recommended for straight installations, and 3mm for herringbone patterns.









ELEB42114





Shade variation: V3 high

ELEB42112



ELIC55901

ELIC55902

ELEB42117



ELIC55903

ELIC55904

ELIC55905

ELEB42113

ELIC55900

1	2	3

Sizes (mm)		Thickness	PTV Wet Slider 96	
1	48x450	9.5	Natural ≥ 36PTV	
2	100x350x48 CORN	9.5	Natural ≥ 36PTV	
3	14x450 QR	9.5	Natural ≥ 36PTV	





Earthbound

Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	Conforms
4	Bending strength	Conforms
8	Linear thermal expansion	a ≤ 7.1x10-6 °C-1
9	Thermal impact resistance	Resistant
11	Glaze crazing resistance	Resistant
12	Frost resistance	Resistant
13	Chemical resistance	Conforms
14	Stain resistance	Class 5
	Slip resistance	R10
	Pendulum test - Slider 96 (Shod) Wet	Natural ≥36PTV

Sustainability information







Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly. Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.